

T49G
8
HDMI
T49G Wi-Fi USB2.0



T49G 1080P T49G 3 200 5

8 T49G 29 T49G T49G

T49G USB2.0 U T49G 4.0
T49G T49G T49G
Wi-Fi T49G HDMI T49G

Yealink T49G T49G H.323 SIP TLS/SSL

8 1280x800 IPS LCD
H.323/SIP
I UQY @hY 2 eU:UQ c YT
H.239/BFCP (SIP)
(
200
4.0
Wi-Fi
78 78 802.11a/b/g/n)
HDMI
U
16
3
5

SIP VP-T49G

HD HD
G.722,G.711(A/μ), G.729AB, G.723, G.726,
Y23 ec
4D 6*9 RQT ec V RQT B63 (SIP INFO
F14 3 7 153 @3 1:2 173

(0 V c
H.264HP, H.264, H.263
200
63.5°
37°

8 1280x800
10

16 F 9@

XML QdY EB EB9
BD3 @HB B63 & FA D3 @HB B63 &

HDMI
U

USB3.0 Cable

H.323/SIP
H.239/BFCP SIP
H.245, H.225, H.235, H.241
SIP
1000

XML/LDAP

29
8

G V 78 78 802.11a/b/g/n
54B

1 USB2.0
1 USB3.0 USB3.0 Cable
1 B:) @3
1 B:) @3
1 HDMI
1

FTP/TFTP/HTTP/HTTPS/PnP
PnP DB @

100~240V 12V/2A
8.0W-12W
(W*D*H*T):
& (
10~95%
-10~50°C

IPv4/IPv6 C9@ B63 f B63 &
STUN

SIP
IP @@@ 5

HTTP/HTTPS

SNTP

E 4@D3 @4 C B F B63 &
A C(A d Q W W F 1 Q Ub D C 4 C3 @
CBD@ TLS

HTTPS

MD5/MD5-SESS
U F @ IEEE802.1X

Yealink SIP VP-T49G IP

ED10
5 PCS
12.9 Kg
14.0 Kg
& &
((&

©2017

©2017

Yealink

Xdt * ce ldi UQY S

Xdt c* dS Udi UQY S

61 A

